
11000 BHP Anchor Handling Tug AHT for Sale File-SB0006



SPECIFICATIONS

Year of Delivery

200

Туре

Ocean Going / Anchor Handling / Towing Tug

Classification

ABS +A1, Towing Vessel, Fire Fighting Vessel Class 1, (E) + AMS, AH **Dimension**

60.0m x 17.8m x 7.5m

Draft

6.0m (Designed) / 6.3m (Max)

Clear Deck Space

25.0m x 14.0m

GRT / NRT / DWT

2610T / 783T / 1545T

Speed

15 knots

Bollard Pull

150T

Endurance

35 days

Accommodation

Fully air conditioned for 28 men Complement : 16 men Pax : 12 men

Lifesaving

Comply to SOLAS requirement

Firefighting

FiFi 1

Fresh Water

386 mt

Freshwater Maker

20 mt/day

Fuel

MGO - 1085 mt

Rig Chain Locker

2 X 103m³ (4.8m X 4.9m X 4.4m)

Main Engines & Gearboxes

2 x 5500 bhp Ulstein Bergen propulsion engine type BRM-9 MCR: 11000bhp at 750 rpm c/w gearbox of 5.69:1 ratio

M.E. Consumption

42,144 litres MGO and 100 litres lube oil per 24 hours at full power. 31,608 litres MGO and 75 litres lube oil per 24 hours at economic cruising speed of 10 knots

Generators

 3×800 KW, 3508B 415/3/50, diesel driven generators.

1 x 300kW, Cat 3408 Dita 415/3/50, radiator-cooled emergency generator,

2 x 1400 kW shaft alternator

Generator Consumption

600 ltrs MGO & 15 ltrs L.O. / 24 hrs

Propulsion

2 x ULSTEIN C.P. propulsion system type 1500 AGSC-KP25-950/4 c/w 4.2mm dia, 4 bladed propeller in kort nozzle

Steering Gear

Ulstein Tenfjord electro hydraulic steering gear, type: 2 x SR662. Torque: 136 kn m each

Lube Oil Purifiers

2 x Mitsubishi self cleaning purifiers with capacity of 2900 litre/hr

MGO Purifiers

2 x Mitsubishi self cleaning fuel oil purifier for MGO, with capacity of 2900 litre/hr

Kamfork Sharkjaws & Guide Pin

Type: 130554 w/bollard pull up to 160T and safe capacity of chain/wire w/size of 102mm and SWL of 500 MBL

Bow Thruster / Stern Thruster

3 x Brunvoll C.P. transverse thruster, 2 Bow, 1 Stern Type : FU-63-LTC-1550-650KW

Thrust: 9.1T

Anchors

2 x 2280kg stockless Bower anchor

Anchor Windlass

1x BRATTVAAG hydraulic windlass Type: BFMG 63.048. Duty of cable lifter: 10T pull at 0-15m/min

Anchor Chain

2 x 440m x 48mm dia. U2 steel stud link chain

Towing/Anchor Winch

BRATVAAG triple drum waterfall hydraulic winch.

Type: BSL 350 WX/2SL 350WX with remote control in wheelhouse 1. At low gear (AH & towing drum) Line pull 1st layer:

350T at 0-9m/min
At low gear Top layer:

150T, 0-20.8m/min 2. At high gear

Line pull - 1st layer: 130T at 0-24.5m/min Line pull - Top layer: 56T at 0-56M/min

Wire Cap:2 x 2000m 83mm dia 1 x 5390m x 83mm dia wire Brake holding : 500T on 1st layer

Tugger Winch

2 x BRATVAAG hydraulic tugger winch type AKM 6318, 18T line pull at 0-43m/min

Capstan

2 x BRATVAAG hydraulic capstan 15T line pull at 0-22 m/min

Wire Storage Reels

2 x 20T line pull at 0-35m/min hydraulic wire storage reels of 2000m x 83mm dia. wire capacity

Fendering

Flat doubler plates of 24" x 25mm cross section welded to side shell. Bow plate of approx 50mm thick section secured vertically

Deck Crane

North American Offshore Crane Model MCT2-2581 2.65T at 24.5m radius. 9 0T at 12m radius

Liferafts 4

x 30 men. Rescue/workboat 1 x 6 persons

Gyro & Automatic Pilot 1

x Gyro-Tokimec TG-6000. Autopilot - Furuno NAV Pilot-500

Radar

1 x FURUNO model FR-2125 c/w 6.5ft scanner, 21" CRT display. 0.25-96 nm range c/w performance monitor

SSR

Radio console, FURUNO model RC-1800-IT-25-250, 24V DC/220V AV c/w DSC & NBDP to meet GMDSS requirements. FURUNO SSB FS2570-250W

VHF

2 x VHF/FM multi-channel marine radio telephones. FURUNO FM-8500-25W

Weather Facsimile

1 x FURUNO Fax-207

Other Navigation Equipment

Inmarsat-C, Inmarsat Mini-M, EPIRB, Radar Transponder, Talk Back/P.A. System, Fog Horn Signal, Navtex Receiver, DGPS Navigator, Echo Sounder, Speed Log, Anemometer, SSAS, GMDSS Hand Held VHF Radio, AIS, Common Battery Telephone system, TV Antenna system, CCTV system.

External Firefighting

FiFi 1. Pump - 2 x 1500 m³/hr and 14 bars

Fire Monitors

Water Monitor – 2 x 1200 m³/hr Foam Monitor – 1 x 200 m³/hr both of manual and remote control and capable of 360□ rotation

Dispersant Booms

2 x 8m dispersant booms fitted

Sewage Treatment Plant

Taiko Kikai SBT-40 for 40 men