

SPECIFICATION OUTLINE 5150BHP HANDYSIZE ASD TUG

Vessel Developer: Vessel Name (IMO No.): Classification Notation:

BV I & HULL & MACH, AUT-UMS, Tug, Escort Tug, Special Service - Utility Vessel, Fire fighting ship 1, Water spraying, Harbour

Operation

Flag:

Year Built: 2019, Ready for delivery

Main Particulars			Main Machin	
	Length O.A.	30.00 m	Main Engine	
	Length B.P.	23.10 m	- Model	
	Beam MLD.	12.00 m	- Model	
	Depth MLD.	5.50 m	- Power	
	Berth	12 Ps	Marine Gen. Sets	
	Harbour Operation /		- Model	
	Escort Draft	3.80 m		
	Offshore Draft	4.50 m (max)	- Power	
	Trial Speed	~13.00 Kn	Habour Gen. Sets	
	GRT	~399 t	- Model	
	NRT	~119 t	D	
			- Power	
			ACD Duonellong	

Main Capacity

F.O.	~240.00 m ³
F.W.	~70.00 m ³
FiFi foam	10.17 m^3
Spilled Oil dispersant	6.51 m^3
Lube Oil	3.04 m^3

Main Escort/Anchoring Equip.

One set Hydraulic Escort/Towing /Anchor Windlass Winch set

- Anchor weight: $2 \times 570 \text{ kg}$
- Diameter of anchor chain : Φ20.5 mm
- Rated hauling speed:1.8t@0~10m/min
- Capacity: φ100mm × 120m (P.P. Wire) (*)
- Brake Holding: 200t
- Rated pull: 30t @ 0~10 m/min

One set Disc type short towing hook

- SWL: 80t

One set Stern Roller

- $\Phi0.8m \times 3.0m$

nery & Propulsion Unit

2 × Caterpillar 3516C (IMO Tier II) 2,575BHP (1920kW)@1,600rpm

2 × Caterpillar C7.1 (IMO Tier II) $150kW / 400V / 50Hz / 3\Phi$ 1 × Cummins - Onan 30MXDGBA

 $30kW / 380V / 50Hz / 3\Phi$

ASD Propellers

- Maker Rolls Royce 2 x US205 P20 FP - Model **Main Pump Sets** Azcue

Oily Water Separator $1 \times 0.5 \text{m}^3/\text{hr}$ 1×15 persons **Sewage Treatment Plant External FIFI System** (BV FI-FI 1 class)

- Maker

- Firefighting Monitor $2 \times 1200/300$ m³/hr (sea water/foam)

 $1 \times 2760 \text{m}^3/\text{hr}@115 \text{mlc}$ - Firefighting Pump

Lifesaving & FiFi Equip.

- Lifesaving & FiFi equipment which are in compliance with the SOLAS requirements, Hong Kong or flag state's Merchant Shipping Ordinance and class notation requirements
- CO₂ Fire Fighting System as per BV Rules
- Electric Fire Bilge Pump Set ability: $2 \times 14 \text{m}^3/\text{hr}$
- Spilled Oil Dispersant Boom

Main Radio & Nav. Equip.

Radar 1×JRC JMA-5212-6 Echo Sounder 1×JRC JFE-380 Speed Log 1×Yokogawa EML 500 Anemometer 1×RM. YOUNG 06206 GPS 1×JRC JLR-7500 Electric Horn 1×Ibuki ES300 GPS Compass 1×JRC JLR-21 Vertical Standard Magnetic Compass 1×CGT-165 Sound Power Tele. 1×12KSL Public address system $1 \times KG-1D$ AIS 1×JRC JHS-183

Bridge Alarm 1×JIAXING KEXUN KBJ -3 VHF telephone 1×JRC JHS 770S NAVTEX 1×JRC NCR-333 SART 1×JOTRON TronSart20 EPIRB 1×JOTRON Tron60S Portable VHF 2×ENTEL HT-649

Air Conditioning System

- -Equipped with centralized air conditioner for Wheelhouse, Mess Room, Captain Room and Chief Eng. Room and other crew rooms.
- Equipped split-type air cooler for engine centralized control room.

Cabin & main living facility

2×Senior Officer Cabin for single 5×Crew Cabin for two men

1×Horizontal dual temperature freezer / refrigerator

2×Single head induction Cooker 1×Centralized electric water heater 80L 1×Track type Wheelhouse chair

(Remarks (*) are as additional items, which are not included in the construction of the actual vessel and furnish. If the buyer of this vessel needs to add these additional items and appoints shipyard to do so, the buyer must additionally pay the fee to the shipyard.)

(Particulars given herein are believed to be correct but not guaranteed. Owners reserve the rights to amend specifications without notification.)

Specification Outline of 5150BHP HANDYSIZE ASD TUG (E)

Updated at 2019/01/03