SPECIFICATIONS

AHTS -110T BP, DPII, FIFI-1, 8320BHP/2x3060KW

DISCHARGE:



Fuel Oil: Drill / Ballast water: Portable / Fresh Water: Liquid Mud / Brine Bulk:

1 x 150 m3 / hr @ 75m head 1 x 150 m3 / hr @ 75m head 1 x 150 m3 / hr @ 75m head 2 x 100 m3 / hr @ 75m head 2 x 23 m3 / hr @ 75m head

ANCHOR HANDLING & TOWING:

Bollard Pull: AHT Winch:

Line Pull:

110 tonnes approx. Double Drum Waterfall type

250.0 T

		Enic Fun.	250.01
GENERAL:		Brake Capacity:	300 t
Year Built:	2012	Drum Capacity:	64mm x 1500m
Builder:	Guangzhou Hangtong Shipbuilding and	Towing Drum:	64mm x 1500m
	Shipping Co Ltd, China	Anchor Handling Drum: Speed:	64mm x 1000m
Classification:	ABS*A1 Offshore Support Vessel(E), AMS, *DPS-2, Fire Fighting Vessel Class 1,	Control:	Remote control from aft control stand in wheelhouse and forecastle deck(Stbd)
	Towing Vessel, All, *ACCU	Stern Roller:	5.5m(length)x2.5m diameter(swl 300mt) "Karm Fork" 300 tonnes SWL with jaw
		Shark Jaws:	plates
Port Of Registry:	LAGOS		for 32 mm to 102mm diameter chain
Flag:	NIGERIA	Towing Pins:	2x300 tonnes SWL, hydraulic operated
DIMENSIONS:		DECK EQUIPMENT:	
Length Overall:	75.00 m approx.	Tugger Winch:	2 x 10 tonnes @15m/min
Length B.P.:	67.28 m	Capstan:	2 x 5 tonnes @ 30m/min
Breadth,Moulded:		16.00 m	Deck Crane:
Depth Moulded:	7.5 m	Rigid Rescue Boat: ANCHORING	1 x 6 person
Draft (MAX):	6.1 m	EQUIPMENT:	
GRT / NRT	2759 T / 827 T	Anchors:	2 x 1982 Kg ,D-14HHP
Draft: DWT at Assigned	2500 T	Cables:	467.5mx44m / grade U2 type anchor chain cables
		Windlass:	1 x Double Gypsy and Warping Ends

MACHINERY:

Main Engine: Main Engine Type:	2 x 4160 BHP	DYNAMIC POSITIONING SYSTEM Wartsila IMO Class DPII System:	
Propellers:	2 Sets,Controllable Pitch Propeller	Maker:	Kongsberg
Rudders:	2	Gyro Compass:	2
Bow Thrusters:	2 x 10T CPP	DGPS:	2
Stern Thrusters:	1 X 10T CPP	Radius 1000	1
Generators: Shaft	2 x 380 KW diesel driven	Anemometer:	3
generators: Emergency	2 X 1500 KW shaft driven	Vertical Referenace Unit:	2
Generator:	1 X 94 KW approx. diesel driven	UPS:	2
		Motion Reference Sensors:	2
CAPACITIES:		Printer:	1
Deck Cargo: Cargo Deck Dimensions: Clear Deck	800 tonnes	Independent Joystick:	1
Space:	500 m2	ACCOMODATION	
Deck Strength:	7.5 tonnes / m2	Total Accomodation:	40 Berths, fully Air-Conditioned
Fuel Oil:	858 m3 approx.	1 Man Cabin:	8
Drill / Ballast Water		1371 m3 approx.	2 Man Cabin:
Portable / Fresh Water:		375 m3 approx.	Officers Mess:
Dry Bulk:	226 m3	Crew Mess:	1
Liquid Mud:	405 m3 approx. (SG 2.5 tonne / m3)	Hospital:	1
Brine:	200 m3 approx.	Office:	1
Base Oil: Rig Chain	Not aplicable	Gymnasium:	1
Lockers:	2 x 80 m3 approx.	NAVIGATION & COMMUN	NICATION:
		Radars:	1 S-Band Radar / 1 X-Band Radar
		GPS With Plotter:	1
		AIS:	1
		Echo Sounder:	1
		Auto Pilot and Steering Ge	par:
		Gyro Compass:	3
		GMDSS: S.S.B.:	1
		Inmarsat C With EGC:	2
		MF/HF-DSC/NBDP Radio:	1
		VHF / DSC:	2

Particulars believed to be correct but not guaranteed. Owners Reserved the Right to amend the specifications without Notifications.